




Specification

Model	1749	Range of Application	Outdoor
Photo.		Dimensions	Cut size
		Φ160*H110 mm	Φ145*H115 mm
Material		Packing Information	
<ol style="list-style-type: none"> 304 Stainless steel cover die-casting aluminum body 8-10mm step tempered glass plastic casting available sillicon sealed gasket 		<ol style="list-style-type: none"> 1 PCS /Inner box 12 PCS/Carton N.W:19.2 KGS , G. W:20.7 KGS Carton size :52*35.5*26.5 CM 	
Installation		Light Source Technical Data	
<p>The fitting is suitable to be installed in restricted accessible areas (E. G. pedestrians and pedal cycles only), Rated load if the fitting is 5KN, Rated maximum surface temperature will be 45°C.</p> <ol style="list-style-type: none"> Using the allen key (supplied) remove the four socket cap screw, Dismantle the fitting . Dig a hole 170mm wide and 130mm deep to accommodate the ground tube. Line the bottom with fine shingle to allow for drainage and leveling of the fitting. Wire installation or replace needs an electric engineer or monitor by an electric engineer. Ensure the ground tube is flush with the surrounding ground and fill the space between the ground tube and the side of the hole flush with concrete. unscrew the gland nut to allow the mains supply cable to feed through Feed the mains cable through the gland nut allowing enough cable to connect to the terminal block on the lampholder assembly. Tighten the gland nut and lower the casing into the ground tube. 		Chip Brand	Bridgelux
		Driver Brand	Done
		Color Temperature	3000K/6000K
		CRI	>70
		Input Voltage	12V AC/DC
		Lens Angle	15 degree
		IP-RATING	IP67
		Electricity-Proof Grade	CLASS 1
		Lamp Power	7W
		Lamp Efficacy	420-500LM
Power Factor	>0.5		