




Specification

Model	1729-SQ-SV	Range of Application	Outdoor
Photo.		Dimension	Cut size
		52*52*H80	Φ48*H90
Material		Packing Information	
<ol style="list-style-type: none"> 1. 304 Stainless steel cover 2. 304 Stainless steel body 3. 6mm step tempered glass 4. plastic casting available 5. silicone sealed gasket 		<ol style="list-style-type: none"> 1. 1 PCS /Inner box 2. 50 PCS/Carton 3. N.W:13.5 KGS , G.W:15 KGS 4. Carton size :33.5*33.5*21.5 CM 	
Installation		Light Source Technical Data	
<p>The fitting is suitable to be installed in restricted accessible areas (E.G. pedestrians and pedal cycles only), Rated load if the fitting is 5KN, Rated maximum surface temperature will be 45°C.</p> <ol style="list-style-type: none"> 1. Using the allen key (supplied) remove the four socket cap screw, Dismantle the fitting . 2. Dig a hole 48mm wide and 90mm deep to accommodate the ground tube. 3. Line the bottom with fine shingle to allow for drainage and leveling of the fitting. 4. Wire installation or replace needs an electric engineer or monitor by an electric engineer. 5. Ensure the ground tube is flush with the surrounding ground and fill the space between the ground tube and the side of the hole flush with concrete. 6. unscrew the gland nut to allow the mains supply cable to feed through 7. Feed the mains cable through the gland nut allowing enough cable to connect to the terminal block on the lampholder assembly. 8. Tighten the gland nut and lower the casing into the ground tube. 9. Fasten the casting onto the ground tube and tighten the fixing screws 		Chip Brand	Bridgelux
		Driver Brand	Done
		Color Temperature	3000K/6000K
		CRI	>70
		Input Voltage	12V AC/DC
		Lens Angle	30 degree
		IP-RATING	IP67
		Electricity-Proof Grade	CLASS 1
		Lamp Power	1W
		Lamp Efficacy	60-80LM
		Power Factor	>0.5