




Specification

Model	1752	Range of Application	Outdoor
Photo.		Dimension	Cut size
		300*90*H105 mm	285*80*H110 mm
Material	Packing Information		
1. 304 Stainless steel cover 2. die-casting aluminum body 3. 8-10mm step tempered glass 4. silicone sealed gasket	1. 1 PCS /Inner box 2. 8 PCS/Carton 3. N.W:17.6 KGS , G.W:19.2 KGS 4. Carton size :33*25*46 CM		
Installation	Light Source Technical Data		
<p>The fitting is suitable to be installed in restricted accessible areas (E.G. pedestrians and pedal cycles only), Rated load if the fitting is 5KN, Rated maximum surface temperature will be 45°C.</p> <p>1. Using the allen key (supplied) remove the four socket cap screw, Dismantle the fitting .</p> <p>2. Dig a hole 170mm wide and 130mm deep to accommodate the ground tube.</p> <p>3. Line the bottom with fine shingle to allow for drainage and leveling of the fitting.</p> <p>4. Wire installation or replace needs an electric engineer or monitor by an electric engineer.</p> <p>5. Ensure the ground tube is flush with the surrounding ground and fill the space between the ground tube and the side of the hole flush with concrete.</p> <p>6. unscrew the gland nut to allow the mains supply cable to feed through</p> <p>7. Feed the mains cable through the gland nut allowing enough cable to connect to the terminal block on the lampholder assembly.</p> <p>8. Tighten the gland nut and lower the casing into the ground tube.</p>	Chip Brand	Bridgelux	
	Driver Brand	Done	
	Color Temperature	3000K/6000K	
	CRI	>70	
	Input Voltage	12V AC	
	Lens Angle	15 degree	
	IP-RATING	IP67	
	Electricity-Proof Grade	CLASS 1	
	Lamp Power	5W	
	Lamp Efficacy	300-350LM	
	Power Factor	>0.5	