



Item 4306

**PUCK LIGHT**  
2,700K - 6,000K LEDs  
LINE VOLTAGE, DIMMABLE

cETLus LISTED

**Product Description**

Series Puck Light has 12 super bright LEDs and can be recessed or surface mounted in any direction. It's Line voltage, high performing, easy to install puck lights with a swivel feature offer over 200 lumens per puck without the need for a driver.

**Features**

- Line voltage, without the need for a driver
- Dimmable with most wall/box dimmers
- Link up to 20 pucks to a single power supply
- Center section swivels for directional light control
- Zinc alloy light housing with aluminum heat sink
- The fitting is supplied with a collar and can be either surface or recess mounted
- Seoul LEDs, over 85% less energy used when comparing to halogen - save money on electricity bills
- cETLus listed

**Construction**

Housing: Zinc Alloy Trim with Steel Collar

Lens: Polycarbonate

**Finish**

Available in White / Black / Stain Nickel / Bronze / Platinum

**Electrical**

This unit is wired for 120V operation. This LED fixture contains a Triac dimmable driver. Dimmable with most standard wall dimmers. On/off switch included.

**Lamping**

LED's are 2,700K-6,000K non-replaceable. Rated for 50,000 hrs. 90+ CRI.

**Certification**

cETLus listed for dry locations.

**Warranty**

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 3 years from date of purchase.

**Recommended Locations**

The following accessories are included with each fixture:

**Single puck kits include:**

- (1) 6" power cord with roll switch
- (1) pucks with 6" lead wire and mounting screws

**Three puck kits include:**

- (1) 6" power cord with roll switch
- (2) pucks with 6" lead wire and 6" tail wire
- (1) puck with a 6" lead wire
- (2) 12" linking cables and mounting screws

**Five puck kits include:**

- (1) 6" power cord with roll switch
- (4) pucks with 6" lead wire and 6" tail wire
- (1) puck with a 6" lead wire
- (4) 12" linking cables and mounting screws

Specifications and dimensions subject to change without notice.

**Specifications**

Code	LEDs	Input Power	Watt	Lumens	CRI	Color Temperature	Dimensions
4306	Seoul	110V	4W	200-240	90+	2,700K-6,000K	Φ 2 3/4" X 1"

**Accessories (Ordered Separately)**

Junction Box (Black & White)  
12-72" Jumper Connector

