

# Mini LED Under Cabinet Light Specification

## 1 Watt Series



### Introduction:

Richee Lighting's LED under cabinet lights are adopted with high quality Epistar LED as the light source. Beautiful aluminum appearance with fashionable structure. Surface and recessed mounted are available. They are widely used in hospitality, as well as in commercial, and residential locales. Richee Lighting's under cabinet lights come with reliable constant-current or constant voltage external drivers which guarantee reliable and excellent electrical performance.

### Applications:


Kitchen Lighting  
Cabinet Lighting  
Furniture Lighting  
Display Case Lighting  
Jewelry Store, Museum, Wall Way  
Hotel, Restaurant,  
Accent Lighting  
Entertainment Places



## Technical Parameters:

Model NO	4104		
Product Picture			
Input:	12V DC		
Power Consumption:	1 Watt		
LED Chip Brand	Epistar		
Lumen output:	115LM		
Dimmable:			
Color Temperature:	Color Rendering index: >80		
CCT	Warm White 2800-3300 / Neutral White 4500-5000K / Cool White 6000-6500K		
Surface Color:	<u>Aluminum Silver</u>		
Beam Angle:	30°		
Operation Temperature:	-40~50 degrees Celsius		
Protection Rating:	IP21 ( Indoor Use Only)		
Material:	aluminum shell and aluminum PCB board		
Installation:	Recessed mounted or Surface mounted		
Certificate:	CE, RoHS		
Warranty	3 Years		

## Product Dimension:

4104		
Ø33*(H)21.5mm		
		

## Input constant voltage 12VDC

Electrical structure: 1 PCB + 1 LED + 350mA current regulator on the PCB


Input voltage: 12V DC;

Input current: /


Power consumption: 1W

One 12V power supply can work with multiple WEDO under cabinet light which are connected in parallel (not in series), but it is limited by the max load of the 12V power supply.

### 1. With Junction Box



### 2. Without Junction Box




## Import notice:

The total power consumption of the lights connected should be less than 90% of the max load of the power supply.

Low heat, no UV or IR light radiation, Environmentally Safe-no Mercury

## Isolux Diagram:

Epistar LED, 5500-6500K



## Packaging Details:

Model NO:	4104	
Net Weight:	0.005kg	
Gross weight:	0.06kg	
Inner box size:	6.0x6.0x5.5cm	
Carton size:	32x32x25cm	
Quantity per carton:	100pcs	