


LED DOB DOWN LIGHT W/J-BOX (Dimmable)



4610-XX-JB



Size: Φ 136x102mm(5.35x4.00")

Characteristics

Certificate	ETL, Energy Star, FCC, Lighting Facts, LM79, LM80
Life time	50,000 hours
Color	2700/3000/4000/5000K
Lumens	700-850lms
CRI	>90
Dimmable	Yes
Power	10.5W
Voltage	120V AC
Description	4" LED DOB Down Light W/J-Box
Item Number	4610-XX-JB

Features

- Energy efficient: save up to 80% in energy costs
- High lumen output
- Mercury-free
- Instant-on light
- Wet location
- 50,000 hours at 70% lumen maintenance rated life
- CCT:2700-6000K
- 5 years manufacturer warranty

Application























Easy to Install in 4 Easy Steps:









- 1. Shut off power before installation, Cut a corresponding hole in the ceiling. A template is provided to assist with laying out the hole location. When running the supply wirs(s), allow an additional 18 in. of wire at each installation in order to make the electrical connections on the room side of the ceiling hole
- 2. Remove the Junction Box Screw(s) holding the Junction Box Cover .Pass the supply wire(s) through the appropriate knockout hole on Junction Box. Make the electrical connections to fit inside Junction Box following the ELECTRICAL CONNECTIONS.Make sure all connections are secure, tuck all wires inside Junction Box and reinstall Junction Box Cover using Junction Box Screws 3. Press the top portion of the Remodel Clips against the side of the Housing Assembly.
- 4.Push the Housing Assembly with the top side of the Remodel Clips through the hole until tight. Continue to push the Housing Assembly until the fixture snaps into place with the trim tight against the ceiling surface.







