

6546-RGB-2815 30 Led/m LED STRIP



Description

6546-RGB-28185 DC12V input WS2815 LED Strip is a new Digital LED Light the circuit can be transmitted up to 5 meters. At same time the circuits can Dual-signal. If one LED is damaged, the following LEDs can still work. It can realize various colorful changing patterns with corresponding controller. You can control the brightness and the color of each LED individually, which allows you to produce amazing and complex effects. It has 30 pcs led per meter and 30 pixels per meter.

Specifications

LED Type	5050(2815) SMD	Input Voltage	12V
LED Brightness	2000-2400 MCD	Energy class	A+
LED Density	30 pcs/m	Ra	---
Pixel Point Quantity	30 pcs /m	IP Grade	IP20/IP54/IP67/IP68
Cuttible Segments	1 Leds/33.3 mm	Warranty	2 Years
PCB Type/Color	3 oz, White/Black PCB	Certification	UL CE RoHS
PCB Width	10 mm		
Reel Length	5 m		

Product Photometrics

Model No	LED Density	Input Voltage	Power	Color	Brightness
6546-RGB-2815	30 led/m	DC 12V	2.2 w/m	RGB	---

Packing Information

Standard Packing Per Bag

5 meters/reel, 1 reel/anti-static bag
G.W. : Non-waterproof-0.08KG

Standard Packing Per Outer Carton

25 bags to 1 inner box, size : 33.5x20x24cm
4 inner boxes to 1 outer carton size: 43x35.5x50.5cm

NOTES:

1. LED Strip maintains a tester tolerance of $\pm 5\%$ on Color Temperature and Lumen, tolerance of ± 3 on CRI-Ra.
2. The test is based on our laboratory and testing equipment.
3. We reserve the right to modify and improve the design of our fixtures without prior notice.