



# Mini LED Linear Downlight Specification

Description

(Fliches High End Mini 5 head LED Linear Downlight

comes complete with an external driver safely encased in a junction box. This product is highly prized for its beautiful exterior, quality and performance. Gorgeous lighting for various applications.


#### Features and Benefits

- Air Tight & Type IC Rated: No housing Required.
- Fast & Easy Installation: Save labor cost.
- Junction Box Included: No additional hardware required
- Lamp Power: 5\*2W
- CRI 90: True color rendering .
- ETL-listed: reliable quality and safe operation.
- Suitable for damp locations.
- Voltage: 100-130V AC perfect Triac dimming

AC277V Non-dimmable

### **Dimension Drawing**

Unit: mm









Item No.: 3007



Input Power	10W
Input Voltage:	100-277V AC, 50/60HZ
Lumen	650-700LM
Halogen Equivalent	70W
Efficiency	65LM/W
CRI	>90Ra
Power Factor	>0.9
LED Chip	SMD3030
Beam Angle	15° /30° /45°
Color Temperature	2700-6500K
Dimension	147*45*49mm
Cutout Size	139*36mm
Dimming	Triac dimming 10-100%
Approved Locations	Insulated ceilings
Air Tight	Yes
Lamp Life	70% light output at 50000hrs
Certification	ETL, cETL,
Warranty	5 years
Qty/ Ctn	20pcs/ ctn
Ctn Size	
Gross Weight	



# **Great Features and Benefits**

- Appearance: Fashion & high quality design, with unique appearance, easier for marketing.
- Body: Use high quality die-cast aluminum heat sink, better heat conducting is the key of the life span;
- LEDs: High brightness & high quality & High CRI LED, which guaranteed high lumen and high quality
- Beam angle: beam angle of 15//30/45°, be avaliable for your different application
- Driver: Isolated LED driver with 5 years warranty.
- Junction Box: Included, install directly in Insulated Ceilings (IC) without any thermal housing.
- UGR: The innovative black anti-glare screen defines emission with luminance control low UGR;
- Application : can climb walls, cross ceilings, literally go everywhere your design wants it to be.

## **Compatible Dimmers**

Lutron : CTCL-153P / DVCL-153P / S-600P / SLV-600P / CN-600P

Levetion: 6674 /6672

## **Family Products**

