


LED Sheet



Description

The 6990-RGB/27K+60K-24V-CRI90 LED sheet series is ideal for light boxes with a depth of >1.57". Its thick PCB board and high quality SMD5050 5 in 1 chips will ensure constant brightness. It is highly versatile, dimmable, and suitable for both lighting and accenting. There are XH-6Y connectors easy for connection and super slim 3M double-side tape with strong adhesive. Create rich color changing effects via controller.

Product Specifications

Input Voltage	24 V DC
Limiting Control Method	CV-Constant Voltage
Power Consumption	57.5W/pc
Beam Angle	120°
Cutable Segments	3inx2in (76mm x 50mm)
LED Sheet Size	1ftx2ft (305*610)
Luminous Flux Maintenance	75,000 hrs
Dimming	DMX PWM, RF PWM, 0-10V, MLV, Incandescent
Warranty	3Years Limited
Certifications	cULus UL Listed,E467088
Operating Temperature	-20° F to 120° F
Mounting	Non-Porous: 3M double sided Tape
LED Chip Type	High Quality SMD 5050 (5 in 1)
LED Density	288 LEDs/pc
Board Type/Color	2 oz Density,White PCB

Nominal CCT/Color	Luminous Flux (lm)	Luminous Efficacy (lm/W)	CRI
2700K	940	72	90+
6500K	1095	83	90+
Red	382	31	
Green	1283	87	
Blue	235	17	



Ordering Guide

Series	CCT	Voltage
6990	XX	XX

1 - Contact Richee for exact warranty period and policy.

2 - Lumen output are measured according to PMS 80, with a tolerance of +/- 5%

3 - Standard package: 5m/roll