



LED Flexible Strip 6584-RGB/CCT Series



LM79
LM80



The 6584-RGB/CCT series has color changing and tunable white in one single strip . Its thick PCB board and high quality 5 in 1 SMD 5050 chips will ensure that it will last and remain bright . It is highly versatile, dimmable, and suitable for both lighting and accenting.



Product Specifications

ITEM		Nominal CCT/WL	Luminous Flux (LM/FT)	Efficacy (lm/w)	CRI	Input Voltage	Reel Length
6584-RGB/(27K-65K)-24V-CRI90	●●	RGB/(27K-65K)	330	75.0	90+	24V DC	16.4ft / 49.2ft
6584-RGB/(Amber-65K)-24V-CRI90	●●	RGB/(Amber-65K)	330	75.0	90+	24V DC	16.4ft / 49.2ft

- Limiting Control Method: CV - Constant Voltage
- Power Consumption: 4.40W/FT
- Beam Angle: 120°
- LED Density: 36 LEDs/ft / 60 LEDs/m
- Dimming: Dmx PWM, RF PWM, 0-10V, MLV Incandescent

- Operating Temperature: -20°F to 120°F
- Mounting Non-Porous: 3M double sided Tape
- Board Type/Color: 3oz Density, White PCB
- Luminous Flux maintenance: 50,000 hrs
- Segment Width: 0.31 in (12 mm)